







GAS PRESSURE SWITCH

Compact, Low Cost, 1.4 to 20 in w.c. Range





Reliable and convenient, the Series 1996 Gas Pressure Switch serves as a compact. low cost switch for gas fired furnaces and equipment. Pressure ranges for both models are ideal for high or low gas pressure interlock. Visible set point and on-off indicators add convenience in servicing. Use either NO or NC contacts on SPDT switch. Bottom connection has both 1/8" female and 1/4" male threads for pipe nipple or coupling. Top connection vents diaphragm chamber to outside or to furnace combustion chamber. Mount switch with diaphragm in a horizontal position and gas pressure connection at bottom. Used with natural, manufactured or LP gas. 10

FEATURES/BENEFITS


- · Visible set point and on-off indicator simplifies operation and trouble shooting
- Compact size and low cost make it ideal for gas fired or gas equipment OEM applications

APPLICATIONS

· Gas furnaces

Natural, manufactured or LP gas applications

MODEL CHART			
Model	Range (in w.c.)	Model	Range (in w.c.)
1996-5	1.4 to 5.5	1996-20	4-20



SPECIFICATIONS

Service: Air. natural and manufactured gas. LP gas.

Wetted Materials: Consult factory.

Temperature Limits: 32 to 110°F (0 to 43.3°C). -30 to 110°F (-34.4 to 43.3°C) for

dry das or dry air.

Pressure Limits: 45 in w.c. (11.2 kPa) continuous; 10 psig (68.95 kPa) surge.

Switch Type: SPDT.

Electrical Rating: 15A @ 120-480 VAC. 60 Hz. Resistive 1/8 H.P. @ 125 VAC. 1/4 H.P. @ 250 VAC 60 Hz.

Electrical Connections: 3 screw type, common, normally open, normally closed. **Process Connections:** 1/8" female NPT or 1/4" male NPT.

Vent Connection: 1/8" female NPT.

Mounting Orientation: Diaphragm in horizontal position. Consult factory for other position orientations.

Set Point Adjustment: Screw type with visible indicator, inside conduit enclosure. Weight: 1 lb 2.3 oz (349 g).

Agency Approvals: CE. CSA. FM. UL.

• Explosion-Proof Alternative: See page 55 (Series 1950) @Explosion-Proof Alternative: See page 55 (Series 1950G) Process Tubing Options: See page 453 (Gage Tubing Accessories)